(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 22 September 2005 (22.09.2005)

PCT

(10) International Publication Number WO 2005/088976 A1

(51) International Patent Classification?: H04N 7/30, 7/32

(21) International Application Number:

PCT/JP2005/004850 V

(22) International Filing Date: 11 March 2005 (11.03,2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:
2004-071399
2005-015847 12 March 2004 (12.03.2004) IP
24 January 2005 (24.01.2005) JP

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, Ohia-ku, Tokyo, 1468501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SUZUKI, Masakl [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP). MAEDA, Mitsuru [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP).

(74) Agent: OHTSUKA, Yasunori, 7th fl., Shuwa Kioicho Park Bldg., 3-6, Kioicho, Chiyoda-ku, Tokyo 1020094 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: MOVING IMAGE CODING APPARATUS, MOVING IMAGE DECODING APPARATUS, CONTROL METHOD THEREFOR, COMPUTER PROGRAM, AND COMPUTER-READABLE STORAGE MEDIUM



(57) Abstract: In this invention, even if final code data is to be generated by selectively discarding code data for each bitplane, errors due to bitplane rounding down operation can be suppressed from being gradually accumulated in predicted data such as P- and B-pictures, thereby preventing a deterioration in image quality. For this purpose, a block segmentation unit (31) segments an input frame into a plurality of blocks, and supplies the respective blocks to a difference computing unit (32). The difference computing unit (32) outputs the blocks to a DWT unit (33) without any change when the intra-frame coding mode is set. When the inter-frame coding mode is set, the difference computing unit (32) outputs the result obtained by computing a difference from predicted data from a motion compensation unit (42) to the DWT unit (33). The frequency component data obtained by the DWT unit (33) and a quantization unit (34) is entropy-coded by an entropy coding unit (35), and a bitplane formed by bit information at the bit position of each component value is coded. A bitplane round-down unit (36) rounds down the code data of bitplanes from the least significant position to an upper bit position such that the resultant code amount becomes equal to or less than a target code amount. A code forming unit then generates code data. Only when the intra-frame coding mode is set, a dequantization unit (39) and inverse DWT unit (40) are executed to update a frame memory (41).

7/0000/2

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.